


# TAILIN

## REINFORCED DEPRESSED CENTRE DISCS FOR STEEL

### A. (Type 27)

- Approved by CNS standard No. 2551
- German DSA standard No. 2335



REINFORCED DEPRESSED CENTRE DISCS FOR STEEL				
Dimensions	Specification	RPM	Code No.	Price \$
4 x1/8 x5/8	A24R2G	15300	635-600	1.40
4 x1/8 x5/8	A24S2G	15300	635-602	1.40
4 x1/4 x5/8	A24R2G	15300	635-604	1.60
4 x1/4 x5/8	A24S2G	15300	635-606	1.60
4-1/2 x1/8 x7/8	A24R2G	13.300	635-608	1.90
4-1/2 x1/8 x7/8	A24S2G	13.300	635-610	1.90
4-1/2 x1/4 x7/8	A24R2G	13.300	635-616	2.10
4-1/2 x1/4 x7/8	A24S2G	13.300	635-612	2.10
5 x1/8 x7/8	A24R2G	12.200	635-618	2.40
5 x1/4 x7/8	A24R2G	12.200	635-620	2.80
5 x1/4 x7/8	A24S2G	12.200	635-621	2.80
7 x1/8 x7/8	A24R2G	8.500	635-622	3.30
7 x1/8 x7/8	A24S2G	8.500	635-624	3.30
7 x1/4 x7/8	A24R2.5G	8.500	635-628	3.80
7 x1/4 x7/8	A24S2.5G	8.500	635-629	3.80
9 x1/8 x7/8	A24R2G	6.500	635-634	4.70
9 x1/4 x7/8	A24R2.5G	6.500	635-640	6.50
9 x1/4 x7/8	A24S2.5G	6.500	635-642	6.50

## CUT-OFF WHEELS FOR STEEL



CUT-OFF WHEELS FOR STEEL				
Dimensions	Specification	RPM	Code No.	Price \$
12 x1/8 x1	A30RBF2G	5000	635-694	7.80
12 x1/8 x1	A30RBF1G	4500	635-696	7.80
12 x1/8 x1	A30RBF2G	6300	635-697	7.80
12 x1/8 x20mm	A30RBF2G	6300	635-700	7.80
12 x7/64 x1	A30RBF2G	6300	635-701	8.32
14 x1/8 x1	A30RBF2G	4300	635-702	9.90
14 x1/8 x1	A30RBF1G	3900	635-704	7.80
14 x7/64 x1	A30RBF2G	5400	635-705	10.40