

Dial Indicators

- Reverse counter
- Stainless steel components
- Rotating bezel with clamp
- Lugback (1/4" hole)
- Interchangeable point
- Conforms to AGD 2 standards



Travel Range	Dial Reading	Grad.	Dial Colour	Code No.	Price \$
1/2"	0-100"	0.001"	White	200718	46.27
1"	0-100"	0.001"	White	200720	40.17
1"	0-50"	0.0005"	White	200755	53.00
2"	0-100"	0.001"	White	200725	102.09

Magnetic Back	
For AGD2 series	200722 22.39

Dial Indicators

- Jewelled bearings
- Reversible contact point is adjustable within 220°
- Fully adjustable bevel/dial face, 1.27" easy to read



Series #1- 1-5/8" dia. dial face
Series #2- 2-1/4" dia. dial face

Mitutoyo Model No.	Range (in./mm)	Grad (in./mm)	Reading	Sowa Code No.	Price \$
1044S	5mm	0.01mm	0-100	841286	136.53
1410S	0.250"	0.001"	0-100	841696	155.00
1411S	0.250"	0.001"	0-50-0	848586	139.75
2046S	10mm	0.01mm	0-100	840249	132.00
2047S-01	10mm	0.01mm	0-50-0	842938	122.55
2414S	0.500"	0.001"	0-100	840417	155.00
2416S-10	1.00"	0.001"	0-100	840255	176.00
2424S-19	2.00"	0.001"	0-100	847987	287.03
2804S-10	0.050"	0.0001"	0-10	840258	234.00
2923S-10	0.050"	0.0001"	0-5-0	840260	229.00
2923SB-10	0.050"	0.0001"	0-5-0	843450	208.55
2971	0.5mm	0.01mm	25-0-25	843498	131.00

"S" = flat crystal & flat back "10" = jewelled bearings "-01" = metric ind. with ANSI specs

Test Indicators

- Jeweled bearings
- Inch units come with 3/8 & 8mm dovetail stems
- Easy to read yellow face
- 32mm and 40mm face diameters available



Vertical

Full Set

Carbide tipped point
DIA. ϕ 2mm

Steel point
DIA. ϕ 1mm

Stem Dia.
Metric 4mm
Inch 0.157"

Holding Bar
Metric 9x9x100mm
Inch 0.25"x0.5"x4"

Swivel Clamp
Metric for ϕ 4mm, & ϕ 8mm Dia.
Inch for 3/8", & 0.157" Dia.

Base Set

Stem Dia.
Metric ϕ 8mm
Inch ϕ 3/8"

Knurled
Clamping Ring

Wrench

Horizontal

	Grad.	Range	Dial Reading	Accuracy	Type	Code No.	Price \$
Inch	0.0001"	0.008"	0-4-0	\pm 0.0001"	Horizontal	7501783	154.28
	0.0001"	0.008"	0-4-0	\pm 0.0001"	Vertical	7501785	175.70
	0.0005"	0.03"	0-15-0	\pm 0.0005"	Horizontal	7501733	148.77
	0.0005"	0.03"	0-15-0	\pm 0.0005"	Vertical	7501735	133.07
	0.0005"	0.03"	0-15-0	\pm 0.0005"	Horizontal/Long Point (1.25")	7501736	205.27
Inch Sets	0.0001"	0.008"	0-4-0	\pm 0.0001"	Horizontal	7501787	185.96
	0.0005"	0.03"	0-15-0	\pm 0.0005"	Horizontal	7501738	227.32

196 Series Dial Indicators

- Inch reading
- Graduation: 0.001"
- Dial reading: 0-100
- Shank Diameter 1/4"
- Accurate, reliable, and simple to operate
- Rugged with few moving parts
- Smooth in operation



Range	Supplied With	Starrett No.	Sowa Code No.	Price \$
0.200"	3 Contact Pts & Adapter, 4 attachments* in Case	196A1Z	628864	441.00
0.200"	3 Contact Pts & Adapter Only	196B1	629144	254.00

*Attachments include clamp, tool post holder, snug and hole attachment

25 Series Dial Indicators

- Lug-on-centre back
- Graduation: 0.001"
- Range: 0.250"
- Shockless hardened steel gear train and jewel bearings
- Contact point is interchangeable
- Easy-to-read dial style



Range per Rev.	Dial Reading	Starrett No.	Sowa Code No.	Price \$
0.100"	0-50-0	25-141J	629457	281.00

Holding Bars

- Scalloped design
- Black oxide coating for corrosion resistance



Shank Dia.	Length	Code No.	Price \$
1/4 x 1/2	4"	7500213	35.16
9mm x 9mm	50mm	7500210	38.47
9mm x 9mm	100mm	7500212	39.50

