Description

Straight Metric Indicator Stem Bushing

Straight Metric Indicator Stem Bushing

- Accepts 8mm stem, converts to 3/8" diameter stem
- · Straight bushing, no head
- 0.500" length
- · Brass, Nickel Plated



ASIMETO

7500320

Select-A-Point Kit

The most useful accessory kit for all dial indicators a complete set of 22 different points, increasing the versatility of your indicators.

· Fits all AGD 1, 2, 3, 4 drop style indicators, 4-48 threads



Description	Code No.	Price \$
Select-A-Point Kit	200820	18.54

Articulating Arm Magnetic Bases

- · Accepts test indicators with dovetail clamping mechanism
- Dial gauges can be held by the 3/8" or 8mm diameter stem or by the lug backing plate
- Arm has 3 articulating joints that can be locked with the single hand knob
- · The rotary knob switches natural magnet on or off
- The precision surfaces and the bottom V are securely

	fastened to the	e ferrous workpiece or mach ry knob is in the on position	,	760	2021
•	Slot: 6.5mm				
•	Working Angle	150°			
•	7602011 does	not have fine adjustment			
	Magnetic Power	Magnetic Base (L x W x H)	Height	Code No.	Price
Π	30 kg	36 x 30 x 35mm	195mm	7602011	79.6
	80 ka	60 v 50 v 55mm	350mm	7602021	226.0

Magnetic Power	Magnetic Base (L x W x H)	Height	Code No.	Price \$
30 kg	36 x 30 x 35mm	195mm	7602011	79.68
80 kg	60 x 50 x 55mm	350mm	7602021	226.04
80 kg	60 x 50 x 55mm	440mm	7602031	99.87
130 kg	117 x 50 x 55mm	690mm	7602051	291.13

Dimensional Data

L1	L2	L3
65mm	55mm	60mm
120mm	105mm	60mm
160mm	140mm	75mm
345mm	230mm	60mm



Hydraulic Magnetic Base

- · Accepts test indicators with dovetail clamping mechanism
- Dial gauges can be held by the 3/8" or 8mm diameter stem or by the lug backing plate
- The rotary knob switches natural magnet on or off
- The precision surfaces and the bottom V are securely fastened to the ferrous workpiece or machine table when the rotary knob is in the on position
- Working Angle 150°



Magnetic Power	Magnetic Base (L x W x H)	Height	Code No.	Price \$
80 kg	60 x 50 x 55mm	385mm	7603010	225.85

Permanent Magnetic Base

- With permanent magnetic base, without On/Off switch
- · Dovetail groove included



ASIMETO

Magnetic Power	Main Body	Main Stem Length	Dia. of Hole	Slot	Code No.	Price \$
17 kg	Ø30 x 25mm	85mm	Ø6mm	6mm	7601120	78.75

Standard Magnetic Bases

- For Indicators with 3/8 stems and or Lug backs with 1/4 hole diameter
- On/Off switch
- 132 lbf Magnetic pull



Model	Pull Action	Code No.	Price \$
With 6" Rod and Universal clamp	132 lbf	7601011	37.08
With 6" Adjustable Rod / Fine Adjustment	132 lbf	7601021	34.00

Standard Magnetic Bases

Base only with M8 threaded hole for uses limited only by your imagination.



ASIMETO

Magnetic Power	Magnetic Base (L x W x H)	Female Thread	Code No.	Price \$
60 kg	60 x 50 x 55mm	M8	7600011	54.24
80 kg	60 x 50 x 55mm (metal switch)	M8	7600012	29.22

STM Magnetic Bases





Standard Model BA-1 Code No.	Price \$	Fine Adj. Model BA-1F Code No.	Price \$
225705	38.81	225700	35.85