

## T444 Outside Micrometers

**Starrett**

- No-glare satin chrome finish which resists rust
- Advanced sleeve design with staggered lines and distinct figures for precise and easy readability
- Balanced frame and thimble design to ensure easy handling and better readability
- Provides quick and easy adjustment
- Graduation: 0.0001"




Range	Starrett No.	Sowa Code No.	Price \$
0-1"	T444.1XRL-1	633913	197.00
1-2"	T444.1XRL-2	633901	233.00
2-3"	T444.1XRL-3	633902	254.00
3-4"	T444.1XRL-4	633961	301.00
4-5"	T444.1XRL-5	633962	324.00
5-6"	T444.1XRL-6	633963	360.00

## Interchangeable Anvil Micrometers

**ASIMETO**

- Ratchet stop
- Locking clamp
- Carbide faces
- Satin chrome finish
- Sizes over 12" have a welded pipe frame



Range	Grad.	Accuracy	Notes	Code No.	Price \$
0-6"	0.001"	± 0.0002"	with 6 Anvils & 5 Standards	7111061	603.89
6-12"	0.001"	± 0.0003"	with 6 Anvils & 6 Standards	7111121	407.45
12-16"	0.001"	± 0.0004"	with 4 Anvils & 2 Standards	7111161	752.05
16-20"	0.001"	± 0.0005"	with 4 Anvils & 2 Standards	7111201	836.60
20-24"	0.001"	± 0.0006"	with 4 Anvils & 2 Standards	7111241	1,289.53
24-28"	0.001"	± 0.0006"	with 4 Anvils & 2 Standards	7111281	1,551.36
28-32"	0.001"	± 0.0007"	with 4 Anvils & 2 Standards	7111321	1,877.70
32-36"	0.001"	± 0.0008"	with 4 Anvils & 2 Standards	7111361	1,531.15
36-40"	0.001"	± 0.0008"	with 4 Anvils & 2 Standards	7111401	2,384.00

Note: The individual anvils are matched as a set with the frame. The accuracy cannot be guaranteed if used with a different frame.

## Interchangeable Anvil Micrometers

**Mitutoyo**

- Graduation: 0.001"
- 6 anvils
- Quick change anvils
- Anvils are microlapped
- 0.250" dia. spindle is microlapped & carbide tipped
- Ratchet stop



Mitutoyo Model No.	Range (in.)	Grad. (in.)	Sowa Code No.	Price \$
104-137	0 - 6"	0.001"	840058	549.00
104-138	6 - 12"	0.001"	840059	943.00
104-201	12 - 18"	0.001"	840062	1,167.00

## Digital Disc Micrometers — Non-Rotating Spindle

**ASIMETO**

- Resolution: 0.00005"/0.001mm
- Non rotating spindle
- Ratchet stop
- Inch/Metric conversion
- Absolute or incremental measuring modes
- Automatic On/Off
- Sizes over 1" come with standard



Range	Accuracy	Notes	Code No.	Price \$
0-1" / 0-25mm	±0.0001"	Disc Diameter 0.79"	7145011	618.22
1-2" / 25-50mm	±0.0002"	Disc Diameter 0.79" with Standard	7145021	676.74
2-3" / 50-75mm	±0.0002"	Disc Diameter 0.79" with Standard	7145031	752.88
3-4" / 75-100mm	±0.0002"	Disc Diameter 0.79" with Standard	7145041	834.79

## Digimatic Disc Micrometer

**Mitutoyo**

- With SPC Output
- Resolution 0.00005"/0.001mm



Mitutoyo Model No.	Range (in.)	Grad (in./mm)	Sowa Code No.	Price \$
323-350	0 - 1"	0.001"/0.01mm	840656	707.00

## 220 Series Mul-T-Anvil Micrometer

**Starrett**

- Graduation: 0.001"
- Balanced frame and thimble design
- Ring-type knurled lock nut
- Interchangeable anvils rigidly held in vise type frame, and are quickly interchanged by a single lock screw adjustment
- Two hardened anvils furnished – round 0.120" diameter (3mm) and flat 0.125" (3mm) and 0.060" (1.5mm) thick – sizes approximate
- Accommodates special anvils up to 5/16" (8mm) thick
- Can be used as height gauge by removing vise jaw
- Satin chrome finish
- Rigid one-piece frame of drop forged steel
- Extremely hard and stable one-piece spindle
- Micro-lapped measuring faces



Range	Starrett No.	Sowa Code No.	Price \$
0-1"	220XFL-1	629813	512.00

## Digital Blade Micrometers

**ASIMETO**

- For measuring the groove diameter of shafts, keyways, and other hard to reach portions
- Ratchet stop
- Non-rotating spindle
- Carbide measuring faces
- Inch/Metric conversion
- Absolute or incremental measuring modes



Range	Resolution	Accuracy	Blade Dimensions Depth x Length	Code No.	Price \$
0-1" / 0-25mm	0.00005" / 0.001mm	±0.0001"	0.030" x 0.250"	7117011	747.70
1-2" / 25-50mm	0.00005" / 0.001mm	±0.0002"	0.030" x 0.250"	7117021	793.87
2-3" / 50-75mm	0.00005" / 0.001mm	±0.0002"	0.030" x 0.250"	7117031	739.68
3-4" / 75-100mm	0.00005" / 0.001mm	±0.0002"	0.030" x 0.250"	7117041	794.26

## Digital Screw Thread Micrometers

**ASIMETO**

- For measuring various screw threads
- Automatic on/off to maximize battery life
- Inch/Metric conversion
- Absolute or incremental measuring modes
- Ratchet stop
- Interchangeable tips are optional
- Non-rotating spindle



Range (in.)	Inch Resolution	Accuracy	Range (mm)	Metric Resolution	Accuracy	Code No.	Price \$
0-1"	0.00005"	±0.0001"	0-25	0.001mm	±0.004mm	7136011	520.70
1-2"	0.00005"	±0.0002"	25-50	0.001mm	±0.004mm	7136021	530.95