

SA16 Collets





Size	Collapse Range (mm)	Collapse Range (in.)	Code No.	Price \$
Metric				
2.0mm			338614	98.37
2.5mm			338616	98.37
3.0mm	2.75-3.0	0.108-0.118	338618	24.99
3.5mm	3.0-3.5	0.118-0.137	338620	98.37
4.0mm	3.5-4.0	0.137-0.157	338622	98.37
4.5mm	4.0-4.5	0.157-0.177	338624	98.37
5.0mm	4.5-5.0	0.177-0.196	338626	24.99
5.5mm	5.0-5.5	0.196-0.216	338628	24.99
6.0mm	5.5-6.0	0.216-0.236	338630	24.99
6.5mm	6.0-6.5	0.236-0.255	338632	24.99
7.0mm	6.5-7.0	0.255-0.275	338634	24.99
7.5mm	7.0-7.5	0.275-0.295	338636	24.99
8.0mm	7.5-8.0	0.295-0.314	338638	24.99
8.5mm	8.0-8.5	0.314-0.334	338640	24.99
9.0mm	8.5-9.0	0.334-0.354	338642	98.37
9.5mm	9.0-9.5	0.354-0.374	338644	24.99
10.0mm	9.5-10.0	0.374-0.393	338646	24.99
10.5mm	10.0-10.5	0.393-0.413	338648	24.99
11.0mm	10.5-11.0	0.413-0.433	338650	24.99
11.5mm	11.0-11.5	0.433-0.452	338652	24.99
12.0mm	11.5-12.0	0.452-0.472	338654	24.99
12.5mm	12.0-12.5	0.472-0.492	338656	98.37
13.0mm	12.5-13.0	0.492-0.511	338658	24.99
13.5mm	13.0-13.5	0.511-0.531	338660	24.99
14.0mm	13.5-14.0	0.531-0.551	338662	24.99
14.5mm	14.0-14.5	0.551-0.570	338664	98.37
15.0mm	14.5-15.0	0.570-0.590	338666	24.99
15.5mm	15.0-15.5	0.590-0.610	338668	24.99
16.0mm	15.5-16.0	0.610-0.629	338670	24.99

Size	Collapse Range (mm)	Collapse Range (in.)	Code No.	Price \$
Inch				
1/8	-	-	338674	24.99
3/16	-	-	338676	98.37
1/4	-	-	338678	24.99
5/16	-	-	338680	24.99
3/8	-	-	338682	24.99
7/16	-	-	338684	24.99
1/2	-	-	338686	24.99
9/16	-	-	338688	24.99
5/8	-	-	338690	24.99

CAT Taper TG Collet Chucks



- DIN coolant through the flange
- Shank traverse ground to obtain optimum accuracy
- Meets or exceeds ANSI specifications
- Wrench not included
- Factory balanced to save spindle life, tool life and increased productivity
- Threaded through holes for a back-up screw (tool stop) or coolant through when removed
- TIR, 0.0006"
- AT2 Taper Accuracy
- RFID chip hole



PREMIUM BALANCE
G6.3 at 25,000rpm
CERTIFICATE INCLUDED
CAT50



PREMIUM BALANCE
G6.3 at 30,000rpm
CERTIFICATE INCLUDED
CAT40

Taper	Collet Series	Collet Range	L	L1	D	Tightening Torque (Nm)	Code No.	Price \$
CAT40								
CT40	TG75	3/64-3/4	3.00	1.61	1.89	81.3	531284	363.75
CT40	TG75	3/64-3/4	5.00	1.61	1.89	81.3	531286	186.05
CT40	TG100	3/64-1	3.00	2.13	2.50	81.3	531288	267.95
CT40	TG100	3/64-1	3.50	2.13	2.50	81.3	531290	267.95
CT40	TG100	3/64-1	5.50	2.13	2.50	81.3	531292	267.95
CT40	TG150	1/2-1-1/2	6.00	2.88	3.50	94.9	531294	267.95
CAT50								
CT50	TG75	3/64-3/4	3.50	1.61	1.89	81.3	531296	256.86
CT50	TG100	3/64-1	3.50	2.13	2.50	81.3	531300	256.86
CT50	TG100	3/64-1	5.50	2.13	2.50	81.3	531302	349.87
CT50	TG100	3/64-1	7.50	2.13	2.50	81.3	531304	484.55
CT50	TG100	3/64-1	10.00	2.13	3.50	81.3	531306	548.42
CT50	TG150	1/2-1-1/2	3.50	2.88	3.50	94.9	531308	381.81
CT50	TG150	1/2-1-1/2	6.00	2.88	3.50	94.9	531310	423.45

BT Taper TG Collet Chucks



- DIN coolant through the flange
- Shank traverse ground to obtain optimum accuracy
- Meets or exceeds ANSI specifications
- Wrench not included
- Factory balanced to save spindle life, tool life and increased productivity
- Threaded through holes for a back-up screw (tool stop) or coolant through when removed
- TIR, 0.0006"
- AT2 Taper Accuracy
- RFID chip hole



PREMIUM BALANCE
G6.3 at 25,000rpm
CERTIFICATE INCLUDED
BT50

PREMIUM BALANCE
G6.3 at 30,000rpm
CERTIFICATE INCLUDED
BT30/40

Taper	Collet Series	Collet Range	L	L1	D	Tightening Torque (Nm)	Code No.	Price \$
BT30								
BT30	TG75	3/64-3/4	2.50	1.61	1.89	81.3	532128‡	363.75
BT30	TG100	3/64-1	3.94	2.24	2.50	81.3	532130‡	195.76
BT40								
BT40	TG75	3/64-3/4	3.00	1.61	1.89	81.3	532132	363.75
BT40	TG100	3/64-1	3.50	2.13	2.50	81.3	532134	195.76
BT40	TG100	3/64-1	5.50	2.13	2.50	81.3	532136	215.20
BT50								
BT50	TG100	3/64-1	4.00	2.13	2.50	81.3	532139	317.95
BT50	TG100	3/64-1	6.00	2.13	2.50	81.3	532140	409.58

‡ Not DIN Coolant