

Rohm Prima Key Type Drill Chucks



Impact resistant key-type drill chuck. Conical/ threaded mount in accordance with DIN ISO ping force due to proven transmission principle by means of drill chuck key. Hardened keyholes and clamping prisms.



Rohm Id. No.	Cap. (in.)	Mount	Chuck Key	O.D. (mm)	Opened Length (mm)	Closed Length (mm)	Code No.	Price \$
072806	1/64-5/32	B10	S1	24	39	47.5	390005	65.01
245586*	1/64-1/4	B10	S1	29.5	43	53	390020	63.83
072811*	1/64-1/4	3/8-24	S1	29.5	42.5	53	390025	63.83
245548	1/64-1/4	B12	S1	29.5	47.5	57.5	390030	37.19
245485*	1/64-5/16	B10	S1	29.5	43	53	390040	37.19
245550*	1/64-5/16	B12	S1	29.5	47.5	57.5	390045	63.83
245552*	1/64-5/16	3/8-24	S1	29.5	42.5	53	390050	63.83
072653*	1/32-3/8	B12	S2	34.5	50	60.5	390070	71.83
317255**	1/32-3/8	3/8-24	S2	34.5	49.5	61	390085	55.85
317256**	1/32-3/8	1/2-20	S2	34.5	49.5	61	390090	59.85
072687	1/32-3/8	B16	S2	42.8	63	77	390100	71.83
072693	1/32-3/8	JT2	S2	42.8	59	75.5	390105	95.76
072897*	1/16-1/2	B12	S2	42.8	58	72	390150	83.80
072800*	1/16-1/2	B16	S2	42.8	63	77	390155	83.80
064527*	1/16-1/2	3/8-24	S2	42.8	59	74	390125	65.17
317257**	1/16-1/2	1/2-20	S2	42.8	59	74	390140	65.17
072818*	1/32-1/2	JT6	S3	52	67.5	86	390165	118.37
072819*	1/32-1/2	JT33	S3	52	67.5	86	390170	118.37
072825	1/32-5/8	B18	S3	56.5	79	98	390195	165.55
072827	1/32-5/8	JT3	S3	56.5	79	98	390200	188.93
072831	3/16-3/4	B22	S4	65	92.5	113.5	390225	331.18
072833	3/16-3/4	JT3	S4	65	82.5	103.5	390230	377.87
072834	3/16-1-1/32	B24	S4	80	120	147	390240	668.99

* Smaller, intermediate sizes primarily for hand-operated percussion drilling machines

** With through hole for right and left hand rotation

Rohm Ball Bearing Drill Chucks



- Bodies and jaws hardened and ground
- One piece gear/scroll ring eliminates loss of clamping torque
- Dependable and accurate performance
- Easy operation
- Extended life



Rohm Id. No.	Cap. (in.)	Mount	Chuck Key	O.D. (in.)	Opened Length (in.)	Closed Length (in.)	Code No.	Price \$
215000	1/32-1/2	JT3	S10	2.24	3.11	3.86	390245	256.21
215001	1/32-5/8	JT3	S10	2.44	3.15	3.94	390250	273.66
215002	3/16-3/4	JT4	S13	2.80	3.82	4.65	390255	652.61

Rohm Chuck Keys



- Hand tools used to tighten and loosen screwed elements
- Manual tools are used for construction and repair work that requires simple execution with low energy use



Rohm Id. No.	Model No.	Jacobs Equiv.	Code No.	Price \$
26411	S1	-	390300	6.64
205989	S2A	-	390315	6.64
309380	S2AT	-	390320	9.30
25835	S3	-	390325	9.30
309382	S3AT	-	390330	11.98
25839	S4	-	390335	11.98
228692	S7	K1	390340	7.77
228693	S8	K30	390345	7.87
228695	S10	K3	390355	9.70
68007	S13	K4	390360	22.86
500694	S14	KG	390365	9.30
500511	S17	K2	390370	5.82
228698	S18	K7	390380	5.57
212057	S19	KK	390385	4.83

Rohm Supra Keyless Drill Chucks



- Self-tightening for higher clamping torque
- High percussion design
- All metal construction for extended life
- Jaws and bodies are hardened and ground
- Rapid clamping and releasing without use of a wrench



Rohm Id. No.	Cap. (in.)	Mount	O.D. (mm)	Opened Length (mm)	Closed Length (mm)	Code No.	Price \$
020089	0-1/4	JT1	35	62.5	68.6	390940	195.50
020147	0-1/4	3/8-24	35	62.5	68.6	390945	182.20
215059*	0-5/16	3/8-24	35	62.5	68.6	390950	140.98
871019	0-5/32	B10	26	45.5	50.8	391176	182.20
871031	0-5/16	B10	35	67	73.5	391177	105.94
871032	0-5/16	B12	35.8	67	73.4	391178	179.56
020093	0-5/16	JT1	35.8	70.5	76.9	390970	114.36
871034	0-5/16	3/8-24	35.8	67	73.4	391179	105.94
871038*	1/64-3/8	3/8-24	35.8	70.5	76.9	390985	152.96
871040	0-3/8	B12	40.2	79.5	86.1	390995	72.28
871041	0-3/8	B16	40.2	82.5	89.1	391000	195.50
871045	0-3/8	1/2-20	40.2	79.5	86.1	391015	114.36
871049*	1/32-1/2	3/8-24	42.5	81.5	89.8	391020	167.58
871050*	1/32-1/2	1/2-20	42.5	81.5	89.8	391025	167.58
871051	1/32-1/2	B16	46	93	101.5	391030	210.14
871052	1/32-1/2	JT2	46	91	99.5	391035	223.44
871054	1/32-1/2	JT6	46	94	102.5	391040	223.44
871053	1/32-1/2	JT33	46	94	102.5	391045	223.44
871055	1/32-1/2	1/2-20	46	93	101.5	391050	157.69
871062	1/8-5/8	1/2-20	46	87.5	97.5	391060	182.20
871063	1/8-5/8	5/8-16	46	87.5	97.5	391065	195.50
871064	1/8-5/8	B16	51	96.5	106.8	391070	223.44
871066	1/8-5/8	JT6	51	96.5	106.8	391075	239.41

* Lightweight version mainly for hand operated drilling machines