

## DM213 Fast Drill Sharpener 13mm Capacity



### Patented Features

- Double-bearing grinding unit (reduces wear)
- Drill tightening design with bearing device
- Adjustable trimming angle

### Standard Accessories

- ER20 Collets, ranged from 2.0mm-13mm (12pcs)
- CBN wheel #200x1pc (for High Speed drill)
- 4mm and 5mm Hexagon (Hex.) wrench x 1pc each

|                        |                     |
|------------------------|---------------------|
| <b>Drill Diameter:</b> | Ø2mm - Ø13mm        |
| <b>Point Angle:</b>    | 85° ~ 140°          |
| <b>Power Supply:</b>   | AC110/AC220 50/60HZ |
| <b>Motor:</b>          | 90W                 |
| <b>RPM:</b>            | 6000rpm             |
| <b>Weight:</b>         | 10 kg               |

### Model DM213

| Code No. | Price \$ |
|----------|----------|
| 326130   | 1,828.26 |

### Replacement Wheels for Model DM213

| Description                    | Code No. | Price \$ |
|--------------------------------|----------|----------|
| CBN Wheel for HSS              | 326141   | 154.09   |
| Diamond Wheel for Carbide      | 326143   | 154.09   |
| CBN Wheel for Drills under 4mm | 326145   | 154.09   |

### ER20 Collets for Model DM213

| Size (mm) | ER20 Code No. | Price \$ | Size (mm) | ER20 Code No. | Price \$ |
|-----------|---------------|----------|-----------|---------------|----------|
| 2.0-2.5*  | 326151        | 46.33    | 7-8       | 337479        | 36.65    |
| 2.5-3*    | 326153        | 46.33    | 8-9       | 337480        | 36.65    |
| 3-4*      | 326155        | 45.24    | 9-10      | 337481        | 36.65    |
| 4-5*      | 326157        | 46.33    | 10-11     | 337482        | 36.65    |
| 5-6       | 337477        | 36.65    | 11-12     | 337483        | 36.65    |
| 6-7       | 337478        | 36.65    | 12-13     | 337484        | 36.65    |

\* 2.5-5mm sizes are specially designed pull-back collets, standard ER20 collets cannot be substituted. 6-13mm sizes are standard ER20.

## DM1226 Fast Drill Sharpener 30mm Capacity



### Patented Features

- Double-bearing grinding unit (reduces wear)
- Drill tightening design with bearing device
- Adjustable trimming angle

### Standard Accessories

- ER40 Collets, ranged from 12mm-26mm (15pcs)  
Optional Collets 8~11mm, 27~30mm
- CBN wheel #200x1pcs (for High Speed drill)
- 4mm and 6mm Hexagon (Hex.) wrench x 1pc each

|                        |                       |
|------------------------|-----------------------|
| <b>Drill Diameter:</b> | Ø8mm - Ø30mm          |
| <b>Point Angle:</b>    | 85° ~ 140°            |
| <b>Power Supply:</b>   | AC110 / AC220 50/60HZ |
| <b>Motor:</b>          | 450W                  |
| <b>RPM:</b>            | 4000rpm               |
| <b>Weight:</b>         | 25 kg                 |

### Model DM1226

| Code No. | Price \$ |
|----------|----------|
| 326134   | 4,185.47 |

### Replacement Wheels for Model DM1226

| Description               | Code No. | Price \$ |
|---------------------------|----------|----------|
| CBN Wheel for HSS         | 326154   | 385.04   |
| Diamond Wheel for Carbide | 326156   | 385.04   |

### ER40 Collets for Model DM1226

| Size (mm) | ER40 Code No. | Price \$ | Size (mm) | ER40 Code No. | Price \$ |
|-----------|---------------|----------|-----------|---------------|----------|
| 7-8*      | 326165        | 52.22    | 19-20     | 337522        | 43.12    |
| 8-9*      | 326166        | 52.22    | 20-21     | 337523        | 43.12    |
| 9-10*     | 326167        | 52.22    | 21-22     | 337524        | 43.12    |
| 10-11*    | 326168        | 52.22    | 22-23     | 337525        | 43.12    |
| 11-12     | 337511        | 43.12    | 23-24     | 337526        | 43.12    |
| 12-13     | 337513        | 43.12    | 24-25     | 337527        | 43.12    |
| 13-14     | 337514        | 43.12    | 25-26     | 337528        | 43.12    |
| 14-15     | 337515        | 43.12    | 26-27*    | 326158        | 52.22    |
| 15-16     | 337517        | 43.12    | 27-28*    | 326159        | 52.22    |
| 16-17     | 337518        | 43.12    | 28-29*    | 326160        | 52.22    |
| 17-18     | 337519        | 43.12    | 29-30*    | 326161        | 52.22    |
| 18-19     | 337521        | 43.12    |           |               |          |

\* Optional 8-11mm & 27-30mm sizes are specially designed for the DM1226, standard ER40 collets cannot be substituted. 12-26mm sizes are standard ER40.