

## Extended Range Dial Test Indicators

ASIMETO

- Jeweled bearing design and resistant to magnetic fields
- Stem diameter: Inch: 3/8", Metric: 8mm
- Carbide contact point swivels 210°



| Range  | Graduation | Dial Reading | Accuracy | Type                    | Code No. | Price \$ |
|--------|------------|--------------|----------|-------------------------|----------|----------|
| 0.060" | 0.001"     | 0-15-0       | ±0.0012" | Horizontal w/ 30mm dial | 7503061  | 203.22   |
| 0.060" | 0.0005"    | 0-15-0       | ±0.0012" | Horizontal w/ 30mm dial | 7503561  | 203.22   |
| 0.060" | 0.0005"    | 0-15-0       | ±0.0012" | Horizontal w/ 38mm dial | 7504561  | 190.55   |
| 0.060" | 0.001"     | 0-15-0       | ±0.0012" | Vertical w/ 30mm dial   | 7503063  | 206.91   |
| 0.060" | 0.0005"    | 0-15-0       | ±0.0012" | Vertical w/ 30mm dial   | 7503563  | 155.93   |
| 0.060" | 0.0005"    | 0-15-0       | ±0.0012" | Vertical w/ 38mm dial   | 7504563  | 182.05   |

## Centering Indicators

ASIMETO

- Operating speed not to exceed 800rpm
- Range: Internal: 5/32" - 12"  
External: Up to 12"
- Includes: 6pc feeler set, centre locating feeler



| Dial Range | Graduation | Accuracy | Stem Dia. | Code No. | Price \$ |
|------------|------------|----------|-----------|----------|----------|
| 0-0.15"    | 0.0005"    | ±0.0002" | 0.375"    | 7469008  | 252.87   |

### Parts

| Description            | Length   | Capacity  | Code No. | Price \$ |
|------------------------|----------|-----------|----------|----------|
| ID Feeler              | 2"/50mm  | 4"/100mm  | 7469012  | 5.41     |
| ID Feeler              | 4"/100mm | 8"/200mm  | 7469013  | 5.27     |
| ID Feeler              | 6"/150mm | 12"/300mm | 7469014  | 5.41     |
| OD Feeler              | 2"/50mm  | 4"/100mm  | 7469015  | 5.41     |
| OD Feeler              | 4"/100mm | 8"/200mm  | 7469016  | 5.41     |
| OD Feeler              | 6"/150mm | 12"/300mm | 7469017  | 5.27     |
| Centre Locating Feeler |          |           | 7469018  | 16.45    |
| Feeling Rod            |          |           | 7469019  | 5.84     |

## Extended Range Dial Test Indicator Sets #1

ASIMETO

- Double the range of most indicators
- Jeweled movement

### Standard Accessories:

- Calibration certificate, instruction manual, warranty card, indicator, wrench
- Height gauge bar with swivel clamp w/ 5/32", 7/32", 1/4" holes
- Axial support with 3/8" stem and dovetail
- Reduction sleeve 3/8" to 5/32"
- Two dovetail stems, 3/8" and 5/32"
- Three contact points: 0.4" (hardened steel), 0.08", 0.12" (Tungsten Carbide) x 5/8" long



| Range  | Graduation | Accuracy | Dial Dia. | Indicator            | Code No. | Price \$ |
|--------|------------|----------|-----------|----------------------|----------|----------|
| 0.060" | 0.0005"    | ±0.0012" | 38mm      | Horizontal (7504561) | 7504811  | 242.51   |
| 0.060" | 0.0005"    | ±0.0012" | 30mm      | Horizontal (7503561) | 7504813  | 235.92   |
| 0.060" | 0.001"     | ±0.0012" | 30mm      | Horizontal (7503061) | 7504815  | 226.17   |

## Extended Range Dial Test Indicator Sets #2

ASIMETO

- Double the range of most indicators
- Jeweled movement

### Standard Accessories:

- Calibration certificate, instruction manual, warranty card, indicator, wrench
- Xtra-Mag magnetic base with 2 universal ball sockets
- Micro-fine adjustment screw
- 3-9/16" extension arm
- Two dovetail stems, 3/8" and 5/32"
- Three contact points: 0.4" (hardened steel), 0.08", 0.12" (Tungsten Carbide) x 5/8" long



| Range  | Graduation | Accuracy | Dial Dia. | Indicator            | Code No. | Price \$ |
|--------|------------|----------|-----------|----------------------|----------|----------|
| 0.060" | 0.0005"    | ±0.0012" | 38mm      | Horizontal (7504561) | 7504821  | 237.70   |

## Dovetail Stem Sets

ASIMETO

- Includes stem and knurled clamping ring
- Used in conjunction with a magnetic base clamp to mount a test indicator with a dovetail



| Size  | Code No. | Price \$ |
|-------|----------|----------|
| 3/8"  | 7500311  | 8.02     |
| 5/32" | 7500313  | 8.02     |