

AGD1 Dial Indicators

- Graduation: Inch: 0.001" Metric: 0.01mm
- Dial face dia. 1.65"
- Jeweled bearings
- Lug Back



ASIMETO

Range	Dial Reading	Range per Rev	Stem Dia.	Code No.	Price \$
0 - 0.25"	0-100	0.1"	3/8	7401061	50.26

Dial Indicators

- Reverse counter
- Stainless steel components
- Rotating bezel with clamp
- Lugback (1/4" hole)
- Interchangeable point
- Conforms to AGD 2 standards



Travel Range	Dial Reading	Grad.	Dial Colour	Code No.	Price \$
1/2"	0-100"	0.001"	White	200718	33.51
1"	0-100"	0.001"	White	200720	28.04
1"	0-50"	0.0005"	White	200755	38.42
2"	0-100"	0.001"	White	200725	73.94

Magnetic Back

For AGD2 series	200722	17.08
-----------------	--------	-------

Holding Bars

- Scaloped design
- Black oxide coating for corrosion resistance



ASIMETO

Shank Dia.	Length	Code No.	Price \$
1/4 x 1/2	4"	7500213	28.78
9mm x 9mm	50mm	7500210	31.67
9mm x 9mm	100mm	7500212	29.26

Test Indicators

- Jeweled bearings
- Inch units come with 3/8 & 8mm dovetail stems
- Easy to read yellow face
- 32mm and 40mm face diameters available



Vertical

Full Set

- Carbide tipped point DIA. ϕ 2mm
- Steel point DIA. ϕ 1mm
- Stem Dia. Metric 4mm Inch 0.157"
- Holding Bar Metric 9x9x100mm Inch 0.25"x0.5"x4"
- Swivel Clamp Metric for ϕ 4mm, & ϕ 8mm Dia. Inch for 3/8", & 0.157" Dia.

Base Set

- Stem Dia. Metric ϕ 8mm Inch ϕ 3/8"
- Knurled Clamping Ring
- Wrench

Grad.	Range	Dial Reading	Accuracy	Type	Code No.	Price \$
Inch						
0.0001"	0.008"	0-4-0	\pm 0.0001"	Horizontal	7501783	129.27
0.0001"	0.008"	0-4-0	\pm 0.0001"	Vertical	7501785	130.15
0.0005"	0.03"	0-15-0	\pm 0.0005"	Horizontal	7501733	110.20
0.0005"	0.03"	0-15-0	\pm 0.0005"	Vertical	7501735	106.11
0.0005"	0.03"	0-15-0	\pm 0.0005"	Horizontal/Long Point (1.25")	7501736	163.67
Inch Sets						
0.0001"	0.008"	0-4-0	\pm 0.0001"	Horizontal	7501787	137.75
0.0005"	0.03"	0-15-0	\pm 0.0005"	Horizontal	7501738	179.17

AGD2 Dial Indicators

- Dial face dia. 2.20"
- Lug Back
- Easy to read dial face



7402265

7402267

ASIMETO

Range	Grad.	Dial Reading	Range per Rev.	Stem Dia.	Code No.	Price \$
Inch						
0-0.05"	0.0001"	0-50-0	0.01"	3/8	7402013	116.04
0-0.05"	0.0001"	10-0	0.01"	3/8	7402011	150.14
0-0.05"	0.0001"	0-5-0	0.01"	3/8	7402015	161.37
0-0.25"	0.0005"	0-25-0	0.05"	3/8	7402065	47.03
0-0.5"	0.0005"	0-50	0.05"	3/8	7402125	47.03
0-1"	0.0005"	0-50	0.05"	3/8	7402265	48.36
0-0.25"	0.001"	0-100	0.1"	3/8	7402061	41.52
0-0.25"	0.001"	0-50-0	0.1"	3/8	7402063	70.25
0-0.5"	0.001"	0-100	0.1"	3/8	7402121	43.23
0-0.5"	0.001"	0-50-0	0.1"	3/8	7402123	55.81
0-1"	0.001"	0-100	0.1"	3/8	7402261	40.28
0-1"	0.001"	0-50-0	0.1"	3/8	7402263	56.00
0-2"	0.001"	0-100	0.1"	3/8	7402511	95.95
Metric						
0-10mm	0.01mm	0-100	1mm	3/8	7402101	109.12
0-25mm	0.01mm	0-50-0	1mm	3/8	7402253	192.45
IP54 Water Proof						
0-0.4"	0.001"	0-100	0.1"	3/8	7402267	104.69
0-0.4"	0.0005"	0-50	0.05"	3/8	7402269	104.69

Test Indicators and Sets

- Available in bezel or dial
- Contact point adjustable through 230°
- Fully jeweled movement
- Extremely light contact pressure
- Clear, easy to read, white face
- Dovetails on top and back for all-around positioning
- Sets include 5/32" and 3/8" mounting shanks and 3/8" bar



Dial Dia. (in.)	Grad. (in.)	Range (in.)	Reading (in.)	Point Length (in.)	Code No.	Price \$
1.250"	0.0005"	0.030"	0-15-0	0.700"	200730	66.81